



|                          |                            |
|--------------------------|----------------------------|
| Luminous Flux (Lumen)    | 4320                       |
| Luminous Efficacy (lm/W) | 130                        |
| IP-rating                | IP40                       |
| Impact Protection (IK)   | IK02 - 0.20 joule          |
| Fixture Connection       | Screwless terminal, 5-Pole |
| Finish of Reflector      | Frosted                    |
| Power factor             | >0.90                      |
| Product Type Category    | LED Panel                  |

## Fixture Information

|                       |                                    |
|-----------------------|------------------------------------|
| Mounting Method       | Recessed                           |
| Unified Glare Rating  | < 25 - for hallways and staircases |
| Optical Cover         | PS (Polystyrene)                   |
| Operating Temperature | -10 to +50                         |
| Emergency Lighting    | No Emergency Unit                  |
| Colour of the Fixture | White                              |
| Housing               | Aluminium                          |
| Colour of material    | White                              |

## Dimensions

|                |             |
|----------------|-------------|
| LED panel size | 62.5x62.5cm |
| Length (mm)    | 620         |
| Width (mm)     | 620         |
| Height (mm)    | 32          |

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|